

Wave Single lever shower mixer for exposed installation #
 WA42300000.. / WA42300000.. / WA42300000.. / WA42300000..
 / WA42300000.. / WA42300000A.. / WA42300000A.. /
 WA42300000A.. ...

|< 113 mm >|



Single lever shower mixer for exposed installation	Dimension	Weight	Order number
Connection type: S-connections, 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Non-return valve in the hose connection			
Colors			
04 Bronze Brushed 10 Chrome High Gloss 34 Gold Polished 46 Black Matt 70 Stainless steel Brushed			
Variant			
Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x165 mm	1.660 kg	WA42300000..
Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x165 mm	1.660 kg	WA42300000..
Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x165 mm	1.660 kg	WA42300000..
Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x165 mm	1.660 kg	WA42300000..
Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II	216x165 mm	1.660 kg	WA42300000..
only for Asian markets, Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 6,5 l/min	216x165 mm	1.660 kg	WA42300000A..
only for Asian markets, Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 6,5 l/min	216x165 mm	1.660 kg	WA42300000A..
only for Asian markets, Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 6,5 l/min	216x165 mm	1.660 kg	WA42300000A..
only for Asian markets, Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 6,5 l/min	216x165 mm	1.660 kg	WA42300000A..
only for Asian markets, Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 6,5 l/min	216x165 mm	1.660 kg	WA42300000A..

Wave Single lever shower mixer for exposed installation #
 WA42300000.. / WA42300000.. / WA42300000.. / WA42300000..
 / WA42300000.. / WA42300000A.. / WA42300000A.. /
 WA42300000A.. ...

|< 113 mm >|

Suitable accessories for Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II, Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24 l/min, Noise class: II

Hand shower 3jet Click! MinusFlow MinusFlow, Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Flow rate 240 x 120 mm (3 bar): 9 l/min, Silicone nubs		0.24 kg	UV0652017
Shower rail 900 100 mm, Hand shower holder: height adjustable	900 x 70 mm	0.36 kg	UV0600004
Shower hose Rotation lock: Yes, Nut shape: Conical, 1600 mm	1600 x 23 mm	0.345 kg	UV0610007
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Hand shower 1jet Spray mode: Rain, Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Hand shower 1jet Spray mode: Rain, Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower 3jet Chrome/White High Gloss, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower 3jet Click! Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.23 kg	UV0650017
Shower hose Rotation lock: Yes, Nut shape: Conical, 1250 mm	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Nut shape: Conical, 1800 mm	1800 x 23 mm	0.37 kg	UV0610008
Shower rail 800 Hand shower holder: height adjustable	810 x 60 mm	1 kg	UV0600005

Text for invitation of tenders

Duravit Wave Single lever shower mixer for exposed installation, Shape: Round, Handle version: lever handle, Operation type: Mechanical, Recommended operating pressure: 1 bar, Temperature control: Ceramic cartridge, Suitable for continuous-flow heater, Non-return valve: in the hose connection, Dimension of connection hose: 1/2", Dimensions of water supply connection: DN 15, Connection type for water supply connection: S-connections, Dimensions (width/length x Depth/Width x Height): 216 x 165 x 113 mm

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Wave Single lever shower mixer for exposed installation #
 WA42300000.. / WA42300000.. / WA42300000.. / WA42300000..
 / WA42300000.. / WA42300000A.. / WA42300000A.. /
 WA42300000A.. ...

|< 113 mm >|

