

Wave Single lever bathtub mixer for exposed installation #
 WA52300000.. / WA52300000.. / WA52300000.. / WA52300000..
 / WA52300000.. / WA52300000A.. / WA52300000A.. /
 WA52300000A.. ...

|< 113 mm >|



Single lever bathtub mixer for exposed installation	Dimension	Weight	Order number
Connection type: S-connections, 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off			
Colors			
04 Bronze Brushed 10 Chrome High Gloss 34 Gold Polished 46 Black Matt 70 Stainless steel Brushed			
Variant			
Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II	216x198 mm	1.930 kg	WA52300000..
Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II	216x198 mm	1.930 kg	WA52300000..
Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II	216x198 mm	1.930 kg	WA52300000..
Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II	216x198 mm	1.930 kg	WA52300000..
Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II	216x198 mm	1.930 kg	WA52300000..
only for Asian markets, Bronze Brushed, Flow rate (3 bar): 17,5 l/min	216x198 mm	1.930 kg	WA52300000A..
only for Asian markets, Chrome, Flow rate (3 bar): 17,5 l/min	216x198 mm	1.930 kg	WA52300000A..
only for Asian markets, Gold Polished, Flow rate (3 bar): 17,5 l/min	216x198 mm	1.930 kg	WA52300000A..
only for Asian markets, Black Matt, Flow rate (3 bar): 17,5 l/min	216x198 mm	1.930 kg	WA52300000A..
only for Asian markets, Stainless steel Brushed, Flow rate (3 bar): 17,5 l/min	216x198 mm	1.930 kg	WA52300000A..
Suitable accessories for Bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II, Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II, Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II, Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II, Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Noise class: II			

Wave Single lever bathtub mixer for exposed installation #
 WA52300000.. / WA52300000.. / WA52300000.. / WA52300000..
 / WA52300000.. / WA52300000A.. / WA52300000A.. /
 WA52300000A.. ...

|< 113 mm >|

Hand shower 3jet Click! MinusFlow MinusFlow, Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Stick hand shower 1jet MinusFlow MinusFlow, Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	187 x 25 mm	0.14 kg	UV0642001
Shower hose Rotation lock: Yes, Nut shape: Conical, 1600 mm	1600 x 23 mm	0.345 kg	UV0610007
Hand shower holder Material: Brass, Hand shower holder: Fixed, Escutcheon shape: Round, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620007
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Hand shower 1jet Spray mode: Rain, Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower 3jet Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Hand shower 1jet Spray mode: Rain, Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower 1jet MinusFlow MinusFlow, Spray mode: Rain, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower 3jet Chrome/White High Gloss, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower 3jet MinusFlow MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower 3jet Click! Spray mode: Rain, Pulse, Mono, Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.23 kg	UV0650017
Stick hand shower 1jet Silicone nubs	197 x 25 mm	0.15 kg	UV0640001
Stick hand shower 1jet Silicone nubs	212 x 22 mm	0.18 kg	UV0640002
Stick hand shower 1jet MinusFlow MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	212 x 22 mm	0.18 kg	UV0642002
Hand shower holder Material: ABS, Hand shower holder: Fixed, Mounting bracket shape: Conical	38 x 58 mm	0.06 kg	UV0620001
Shower hose Rotation lock: Yes, Nut shape: Conical, 1250 mm	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Nut shape: Conical, 1800 mm	1800 x 23 mm	0.37 kg	UV0610008
Hand shower holder Material: Brass, Hand shower holder: Fixed, Escutcheon shape: Square, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620026

Text for invitation of tenders

Duravit Wave Single lever bathtub mixer for exposed installation, Shape: Round, Handle version: lever handle, Number of handles: 2, Operation type: Mechanical, Technical features: EasyClean, AirPlus, Recommended operating pressure: 1 bar, Temperature control: Ceramic cartridge, Number of outlets: 2, Consumer selection: Tub filler, Hand shower, Suitable for continuous-flow heater, Non-return valve: in the hose connection, Dimension of connection hose: 1/2", Dimensions of water supply connection: DN 15, Connection type for water supply connection: S-connections, Dimensions (width/length x Depth/Width x Height): 216 x 198 x 113 mm

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Wave Single lever bathtub mixer for exposed installation #
 WA52300000.. / WA52300000.. / WA52300000.. / WA52300000..
 / WA52300000.. / WA52300000A.. / WA52300000A.. /
 WA52300000A.. ...

| < 113 mm > |

