

Wave Bathtub thermostat for exposed installation #
 WA52200000.. / WA52200000.. / WA52200000.. / WA52200000..
 WA52200000.. / WA52200000A.. / WA52200000A.. / WA52200000A..

| < 42 mm > |

...



Bathtub thermostat for exposed installation	Dimension	Weight	Order number
Connection type: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Shut-off and diverter valve, Flow rate (3 bar): 18 l/min			
Colors			
04 Bronze Brushed 10 Chrome High Gloss 34 Gold Polished 46 Black Matt 70 Stainless steel Brushed			
Variant			
Bronze Brushed, Noise class: II	303x223 mm	2.580 kg	WA52200000..
Chrome, Noise class: II	303x223 mm	2.580 kg	WA52200000..
Gold Polished, Noise class: II	303x223 mm	2.580 kg	WA52200000..
Black Matt, Noise class: II	303x223 mm	2.580 kg	WA52200000..
Stainless steel Brushed, Noise class: II	303x223 mm	2.580 kg	WA52200000..
only for Asian markets, Bronze Brushed, Flow rate (3 bar): 16,5 l/min	303x223 mm	2.580 kg	WA52200000A..
only for Asian markets, Chrome, Flow rate (3 bar): 16,5 l/min	303x223 mm	2.580 kg	WA52200000A..
only for Asian markets, Gold Polished, Flow rate (3 bar): 16,5 l/min	303x223 mm	2.580 kg	WA52200000A..
only for Asian markets, Black Matt, Flow rate (3 bar): 16,5 l/min	303x223 mm	2.580 kg	WA52200000A..
only for Asian markets, Stainless steel Brushed, Flow rate (3 bar): 16,5 l/min	303x223 mm	2.580 kg	WA52200000A..
Text for invitation of tenders			
Duravit Wave Bathtub thermostat for exposed installation, Shape: Round, Handle version: lever handle, Operation type: Mechanical, Technical features: EasyClean, AirPlus, HeatLock, Flow rate (3 bar): 18 l/min, Recommended operating pressure: 1 bar, Temperature control: Thermostat cartridge, Suitable for continuous-flow heater, Safety lock at 38 °C, Non-return valve: in the hose connection, Dimension of connection hose: 1/2", Dimensions of water supply connection: DN 15, Connection type for water supply connection: S-connections			

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Wave Bathtub thermostat for exposed installation

|< 42 mm >|

WA52200000.. / WA52200000.. / WA52200000.. / WA52200000..
WA52200000.. / WA52200000A.. / WA52200000A.. / WA52200000A..

...

