

Thermostats Thermostat for concealed installation, 2 outlets #
TH42000140.. / TH42000140.. / TH42000140.. / TH42000140.. /
TH42000140..

|< 170 mm >|



Thermostat for concealed installation, 2 outlets	Dimension	Weight	Order number
Number of outlets: 2, Connection type: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,5 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts			
Colors			
04 Bronze Brushed 10 Chrome High Gloss 34 Gold Polished 46 Black Matt 70 Stainless steel Brushed			
Variant			
Bronze Brushed	170x94 mm	1.800 kg	TH42000140..
Chrome	170x94 mm	1.800 kg	TH42000140..
Gold Polished	170x94 mm	1.800 kg	TH42000140..
Black Matt	170x94 mm	1.800 kg	TH42000140..
Stainless steel Brushed	170x94 mm	1.800 kg	TH42000140..
Necessary accessory			
Basic Set Bluebox® 3/4" Shut-off valve: Yes	164 x 105 mm	1.4 kg	GK0900001
Basic Set Shut-off valve: No	164 x 105 mm	1.24 kg	GK0900000

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Thermostats Thermostat for concealed installation, 2 outlets #
 TH42000140.. / TH42000140.. / TH42000140.. / TH42000140.. /
 TH42000140..

| < 170 mm > |

