Thermostats Thermostatic concealed installation set

|< 170 mm >|

TH42000080.. / TH42000080.. / TH42000080.. / TH42000080.. / TH42000080..



Thermostatic concealed installation set	Dimension	Weight	Order number
Number of outlets: 2, Connection type: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 24 l/min, Escutcheon shape: Round, Including functional unit, Including trim parts			
Colors			
04 Bronze Brushed 10 Chrome High Gloss 34 Gold Polished 46 Black Matt 70 Stainless steel Brushed			
Variant			
Bronze Brushed	170x73 mm	2.320 kg	TH42000080..
Chrome	170x73 mm	2.320 kg	TH42000080..
Gold Polished	170x73 mm	2.320 kg	TH42000080..
Black Matt	170x73 mm	2.320 kg	TH42000080..
Stainless steel Brushed	170x73 mm	2.320 kg	TH42000080..

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Thermostats Thermostatic concealed installation set # |< 170 mm >|

TH42000080.. / TH42000080.. / TH42000080.. / TH42000080.. / TH42000080..

