Balcoon Single lever bathtub mixer for exposed installation

|< 119 mm >|

BA52300000.. / BA52300000.. / BA52300000..



Single lever bathtub mixer for exposed installation	Dimension	Weight	Order number
Connection type: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve			
Colors			
10 Chrome High Gloss 46 Black Matt 70 Stainless steel Brushed			
Variant			
Chrome, Connection type: S-connections, 1/2", Flow rate (3 bar): 21,5 l/min	251x228 mm	1.340 kg	BA52300000..
Black Matt, Connection type: S-connections, 1/2", Flow rate (3 bar): 21,5 l/min	251x228 mm	1.340 kg	BA52300000..
Stainless steel Brushed, Connection type: S-connections, 1/2", Flow rate (3 bar): 21,5 l/min	251x228 mm	1.340 kg	BA52300000..
Text for invitation of tenders			
Duravit Balcoon Single lever bathtub mixer for exposed installation, Designer: Patricia Urquiola, Shape: Round, Handle version: lever handle, Number of handles: 2, Operation type: Mechanical, Technical features: AirPlus, Recommended operating pressure: 1 bar, Temperature control: Ceramic cartridge, Number of outlets: 2, Suitable for continous-flow heater, Dimension of connection hose: 1/2", Dimensions of water supply connection: DN 15, Dimensions (width/length x Depth/Width x Height): 251 x 228 x 119 mm			

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Balcoon Single lever bathtub mixer for exposed installation # |< 119 mm >|
BA52300000.. / BA52300000.. / BA52300000..

